

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 1 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

SECTION 1: Identification

Product Identifier

Product Name: Rigid 4000 Resin

Product code: FLRGWH01

Recommended Use of the Chemical and Restrictions on Use:

Recommended Uses: For use in Formlabs SLA Printers.

Restrictions on Use: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

Formlabs, Inc

35 Medford St

Suite 201 Somerville, MA 02143

+1 617 855 0762

sds@formlabs.com

Emergency Telephone Number:

United States

CHEMTREC

1-800-424-9300 (24/7)

SECTION 2: Hazard Identification

Classification of the chemical in accordance with paragraph (d) of § 1910.1200:

Skin irritation, category 2

Eye irritation, category 2A

Skin sensitization, category 1

Specific target organ toxicity - single exposure, category 3, respiratory tract irritation

Label elements

Hazard Symbol(s):



Signal Word: Warning

Hazard statement(s):

H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H335 May cause respiratory irritation

Precautionary Statement(s):

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves, protective clothing and eye protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing must not be allowed out of the workplace.

P271 Use only outdoors or in a well-ventilated area.

P332+P313 If skin irritation occurs: Get medical advice/attention.

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 2 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

P362+P364 Take off contaminated clothing and wash it before reuse.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 If you feel unwell, contact a doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents and container in accordance with federal, state and local regulations.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: Trade Secret	Methacrylate Monomer(s)	10-20
CAS Number: Trade Secret	Methacrylate Monomer(s)	10-20
CAS Number: Trade Secret	Urethane Dimethacrylate	35-55
CAS Number: Trade Secret	Photoinitiator	<1

Additional information: No additional information

SECTION 4: First Aid Measures

Description of Necessary Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention

After Eye Contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention

After Ingestion:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Skin contact may result in redness, pain, burning and inflammation

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 3 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis

Inhalation may have adverse effects on the respiratory tract. Symptoms may include cough, breathing difficulties, sore throat and inflammation of the mucous membrane lining the respiratory tract

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time)

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Immediate Medical Attention:

If respiratory symptoms persist, seek medical attention

Special Treatment:

No additional information.

Notes for the Doctor:

Treat symptomatically

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam

Unsuitable Extinguishing Media:

Do not use water jet

Specific Hazards Arising From The Chemical:

Thermal decomposition may produce irritating/toxic fumes/gases

Special Protective Equipment and Precautions for Fire-Fighters

Special Protective Equipment:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode

Special precautions

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13)

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 4 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

No occupational exposure limits noted for the ingredient(s).

Biological Limit Values:

No biological exposure limits noted for the ingredient(s).

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Individual Protection Measures, Such as Personal Protective Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 5 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

Physical state	Liquid
Color	Grey
Odor (includes odor threshold)	Characteristic acrylate
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	> 100°C
Flammability	Not Flammable
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Flash point	> 93.5°C
Auto-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
pH	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Vapor pressure (includes evaporation rate)	Not determined or not available.
Density and/or relative density	1.26 g/cm ³
Relative vapor density	Not determined or not available.
Particle characteristics	Not determined or not available.

Other Information

Dynamic Viscosity	2590 cps @ 25°C
-------------------	-----------------

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions, including those associated with foreseeable emergencies:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Avoid storage >38°C (100°F) and exposure to light/direct sunlight and heat.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

Polymerization initiators, including peroxides, strong oxidizing agents, alcohols, copper, copper alloys, carbon steel, iron, rust, and strong bases.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 6 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

Name	Route	Result
Methacrylate Monomer(s)	oral	LD50 Rat: $\geq$ 2000 mg/kg
		LD50 Rat: > 2000 mg/kg
	dermal	LD50 Rabbit: >5000 mg/kg
		LD50 Rat: > 2000 mg/kg
Urethane Dimethacrylate	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg
Photoinitiator	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rat: $\geq$ 2000 mg/kg

Skin Corrosion/Irritation

Assessment:

Causes skin irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	Causes serious eye irritation.
	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment:

May cause an allergic skin reaction.

Product Data:

No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	May cause an allergic skin reaction.
	May cause an allergic skin reaction.
Urethane Dimethacrylate	May cause an allergic skin reaction.
Photoinitiator	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC):

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 7 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

Name	Classification
Methacrylate Monomer(s)	Not Applicable
	Not Applicable
Urethane Dimethacrylate	Not Applicable
Photoinitiator	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Methacrylate Monomer(s)	Not Applicable
	Not Applicable
Urethane Dimethacrylate	Not Applicable
Photoinitiator	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Assessment:

May cause respiratory irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Interactive effects:

No additional information.

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 8 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

Other Information:

No additional information.

SECTION 12: Ecological Information

Ecotoxicity

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	Aquatic Plants EC50 Pseudokirchneriella subcapitata: >97.2 mg/L (72 hr [growth rate])
	Fish LC50 Psetta maxima: 833 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: >143 mg/L (48 hr [mobility])
	Fish LC50 Danio rerio: 0.144 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 2.63 mg/L (48 hr [read-across])
Urethane Dimethacrylate	Fish LC50 Danio rerio: 10.1 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: > 1.2 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Desmodesmus subspicatus: > 0.68 mg/L (72 hr [growth rate])
Photoinitiator	Aquatic Plants EC50 Desmodesmus subspicatus: 1.01 mg/L (72 hr [growth rate])
	Fish LC50 Danio rerio: 1.89 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 2.26 mg/L (48 hr [mobility])

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	The substance is readily biodegradable. 81% degradation in water, measured by BOD, after 28 days.
Methacrylate Monomer(s)	The substance is not readily biodegradable based on test results for an analogous substance. 28.1% degradation in water after 28 days.
Urethane Dimethacrylate	The substance is not readily biodegradable. 22% degradation in water, measured by CO2 evolution, after 28 days.
Photoinitiator	The substance is not readily biodegradable. <10 % degradation in water, measured by O2 consumption, after 28 days.

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	Low potential to bioaccumulate (BCF: 3.2; Log kow: 1.21)

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 9 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

Name	Result
Methacrylate Monomer(s)	The substance is expected to bioaccumulate in organisms. BCF (aquatic species): 1 493 L/kg ww
Urethane Dimethacrylate	The substance has the potential to bioaccumulate (log Pow: 3.39 at 20 °C).
Photoinitiator	The substance is not expected to bioaccumulate (log Kow: 2.91 at 25 °C).

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Methacrylate Monomer(s)	The substance has a low potential for adsorption to soil or sediments based on high water solubility, a low vapor pressure (0.11 hPa @ 20 deg C), and low log Kow (0.97).
Methacrylate Monomer(s)	This substance moderate potential to be adsorbed by the soil.
Methacrylate Monomer(s)	The substance is slightly mobile in soil with a high potential for adsorption to soil and sediment. Koc at 20 °C: 8674
Urethane Dimethacrylate	The substance is slightly mobile, therefore, adsorption to soil and sediment is expected (log Koc: 3.655 dimensionless at 25 °C, QSAR substance data).
Photoinitiator	The substance is slightly mobile, therefore, adsorption to soil and sediment is expected (log Koc: 3.07 dimensionless at 26 °C).

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Methacrylate Monomer(s)	The substance is not PBT.
Methacrylate Monomer(s)	This substance is not PBT.
Urethane Dimethacrylate	The substance is not PBT.
Photoinitiator	The substance is not PBT.

vPvB assessment:

Methacrylate Monomer(s)	The substance is not vPvB.
Methacrylate Monomer(s)	This substance is not vPvB.
Urethane Dimethacrylate	The substance is not vPvB.
Photoinitiator	The substance is not vPvB.

Other Adverse Effects: No additional information.

SECTION 13: Disposal Considerations

Disposal Methods:

As supplied, this material is not considered a hazardous waste under RCRA. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Do not discharge into public wastewater or surface waters. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

Contaminated packaging:

Dispose contaminated packages in a safe manner in accordance with local and national regulations. Do

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 10 of 12


Revision date: 03.27.2026

Rigid 4000 Resin


not allow the product to be released into the environment.

SECTION 14: Transport Information


United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	UN 3082
UN Proper Shipping Name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate
UN Transport Hazard Class(es)	9 
Packing Group	III
Environmental Hazards	Marine Pollutant
Special Precautions for User	None
Additional Information	DOT: 49 CFR 171.4(c)(2) Not regulated as dangerous goods when transported in single or inner packaging of 5 L or less for liquids or net mass of 5 Kg or less for solids provided the packaging meets the requirements of 49 CFR 173.24(a)

International Maritime Dangerous Goods (IMDG)

UN Number	UN 3082
UN Proper Shipping Name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate
UN Transport Hazard Class(es)	9 
Packing Group	III
Environmental Hazards	Marine Pollutant
Special Precautions for User	None
Additional Information	This product is not regulated as a dangerous good when transported in sizes of ≤5L provided the packaging meets the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate
UN Transport Hazard Class(es)	9 
Packing Group	III
Environmental Hazards	Marine Pollutant
Special Precautions for User	None
Additional Information	This product is not regulated as a dangerous good when transported in sizes of ≤5L provided the packaging meets the general provisions of 5.0.2.4.1, 5.0.2.6.1 and 5.0.2.8.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	Not Applicable
-----------	----------------

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 11 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

Ship Type	Not Applicable
Pollution Category	Not Applicable

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA):

Trade Secret	Methacrylate Monomer(s)	Listed - Active
Trade Secret	Methacrylate Monomer(s)	Listed - Active
Trade Secret	Urethane Dimethacrylate	Listed - Active
Trade Secret	Photoinitiator	Listed

Significant New Use Rule (TSCA Section 5):

Trade Secret	Methacrylate Monomer(s)	Not Listed
Trade Secret	Methacrylate Monomer(s)	Listed
Trade Secret	Urethane Dimethacrylate	Not Listed
Trade Secret	Photoinitiator	Not Listed

Export Notification under TSCA Section 12(b):

Trade Secret	Methacrylate Monomer(s)	Not Listed
Trade Secret	Methacrylate Monomer(s)	Listed
Trade Secret	Urethane Dimethacrylate	Not Listed
Trade Secret	Photoinitiator	Not Listed

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals: None of the ingredients are listed.

CERCLA: None of the ingredients are listed.

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know: None of the ingredients are listed.

New Jersey Right to Know: None of the ingredients are listed.

New York Right to Know: None of the ingredients are listed.

Pennsylvania Right to Know: None of the ingredients are listed.

California Proposition 65: None of the ingredients are listed.

Additional information: No additional information.

SECTION 16: Other Information

Disclaimer:

This product has been classified in accordance with OSHA HCS 2024 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The

Safety Data Sheet

US Hazard Communication Standard 2024 (29 CFR 1910.1200)

Initial Preparation Date: 10.19.2020

Page 12 of 12

Revision date: 03.27.2026

Rigid 4000 Resin

information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-1-0

HMIS: 2-1-0

Initial Preparation Date: 10.19.2020

Revision date: 03.27.2026

Revision Notes:

Revision Date	Notes
2026-03-27	Version 1.1 - supersedes Version 1.0

End of Safety Data Sheet